

---

# Intex Krystal Clear Saltwater System Manual

---

*Intex Krystal  
Clear  
Saltwater  
System  
Manual*

*Downloaded from  
[template-dev.mobaptist.org](http://template-dev.mobaptist.org)  
by Leonidas & Melody*

---

## **UNDERSTANDING YOUR INTEX KRYSTAL CLEAR SALTWATER SYSTEM MANUAL: A COMPLETE GUIDE TO SETUP, OPERATION, AND MAINTENANCE**

---

If you have recently purchased an Intex above-ground pool and decided to upgrade your water sanitization system, you have likely encountered the Intex Krystal Clear Saltwater

System. This popular and effective chlorination unit helps pool owners maintain crystal-clear water with less effort than traditional chlorine treatments. However, to get the most out of your saltwater system, it is essential to understand the instructions provided in the Intex Krystal Clear Saltwater System Manual. Whether you are a first-time pool owner or an experienced operator, this guide will walk you through everything you need to know about

installing, using, and troubleshooting your system.

---

## **WHAT IS THE INTEX KRYSTAL CLEAR SALTWATER SYSTEM?**

---

The Intex Krystal Clear Saltwater System is an above-ground pool chlorinator that uses a process called electrolysis to convert dissolved salt in your pool water into natural chlorine. This eliminates the need to buy, store, and add harsh chemical chlorine tablets or granules on a regular basis. The system works with your existing pool pump and filter to circulate water through a salt cell, where a low-voltage electrical current transforms salt into free chlorine that sanitizes your pool

water effectively.

Models vary by size and flow rate, but most follow the same general principles outlined in the Intex Krystal Clear Saltwater System Manual. Understanding these principles is the first step toward trouble-free pool maintenance.

---

## **UNBOXING AND IDENTIFYING KEY COMPONENTS**

---

Before you begin installation, open your box and verify that all parts are present. Your Intex Krystal Clear Saltwater System Manual will list the following components:

- **Main control unit** with digital display and buttons
- **Salt cell chamber** containing

## INSTALLATION

- **Two rubber couplings** with hose clamps for connecting to 1.25-inch or 1.5-inch hoses
- **Power supply** with an appropriate plug for your region
- **Test strips** for measuring salt levels and pH
- **User manual and warranty card**

Keep the box and packaging materials in case you need to store or return the unit. Most importantly, store the Intex Krystal Clear Saltwater System Manual in a safe but accessible location, as you will need to reference it during initial setup and seasonal maintenance.

---

## STEP-BY-STEP SETUP

---

# Choosing the Right Location

The system should be installed after the pump and before the return line to the pool. This ensures that water is already filtered before it enters the salt cell. Place the control unit on a flat, stable surface at least three feet from the pool edge and away from direct rain or sprinklers. The Intex Krystal Clear Saltwater System Manual emphasizes that the power supply must be plugged into a Ground Fault Circuit Interrupter (GFCI) outlet for safety.

# Connecting the Hoses

Most Intex pool pumps use 1.25-inch hoses, while some larger models use 1.5-inch hoses. Your saltwater system kit includes adapters or couplings to fit both sizes. Here is the general process:

1. Cut the return hose at a convenient location between the pump and the pool inlet.
2. Slide the rubber coupling and hose clamp onto each cut end of the hose.
3. Insert the ends of the hose onto the salt cell chamber, which

has barbed fittings.

4. Tighten the hose clamps securely using a screwdriver. Do not overtighten, as this can crack the fittings.
5. Check the **Intex Krystal Clear Saltwater System Manual** for a diagram showing flow direction. The chamber has an arrow indicating the correct water flow path.

## Mounting the Control

# Unit

The control unit can be mounted on a wall using the integrated keyhole slots, or it can sit on a level surface. Ensure that the power cord reaches your GFCI outlet without stretching. Never use an extension cord with this device, as the manual clearly warns against it due to fire and shock hazards.

# Electrical Connections

Insert the power cord from the salt cell chamber into the control unit. This connection is water-resistant but should be kept dry. Plug the control unit into the

GFCI outlet. Once powered on, the digital display will light up, and you can begin adjusting settings.

## **ADDING SALT AND ACHIEVING THE CORRECT SALINITY**

Your pool water must contain a specific amount of salt for the system to function properly. The Intex Krystal Clear Saltwater System Manual specifies a target salt level of about 3000 parts per million (ppm), with an acceptable range of 2500 to 3500 ppm. Pool salt (sodium chloride) must be at least 99.8% pure. Do not use table salt, rock salt, or salt with added iodine or anti-caking agents.

# How to Calculate the Amount of Salt Needed

Use the following formula based on your pool volume:

- Measure your pool's length, width, and average depth in feet.
- Multiply these three numbers, then multiply by 7.5 to get the volume in gallons.
- Divide your pool volume by 1000.
- Multiply that

number by 2.5 to get the pounds of salt needed to reach 3000 ppm from zero.

For example, a 15-foot round pool that is 48 inches deep holds about 4500 gallons. You would need roughly 45 pounds of salt to reach the target level. Always add salt gradually and allow it to dissolve fully before testing. The **Intex Krystal Clear Saltwater System Manual** recommends adding salt directly to the pool water while the pump is running, but do not pour salt into the skimmer or directly into the salt cell.

---

## INITIAL START-UP AND PROGRAMMING

---

Once the salt is

dissolved and the water is circulating, you can power on the system. The control unit features a digital display with buttons for adjusting settings. Here is what you need to do:

1. Press the power button to turn on the unit.
2. Use the up and down arrows to select the appropriate output level based on your pool size and current water temperature. The manual provides a chart to guide you.
3. Set the timer if you wish to run the system only during specific hours. For initial startup, run the system continuously for

24 to 48 hours to establish a chlorine residual.

4. Test the water after 24 hours using the included test strips or a digital tester. Adjust the output level as needed.

The **Intex Krystal Clear Saltwater System Manual** emphasizes that the system will automatically shut off if the water flow is interrupted or if the salt level drops too low. This protects the cell from damage.

---

### **ROUTINE OPERATION AND WATER CHEMISTRY**

---

Running a saltwater pool is not entirely hands-off. You still need to monitor and adjust water chemistry

regularly. The Intex Krystal Clear Saltwater System Manual recommends checking the following parameters at least twice a week:

## Free Chlorine

Maintain free chlorine levels between 1 and 3 ppm. Because the system generates chlorine continuously, you will rarely need to add shock treatments unless you have heavy bather loads or after heavy rain. If levels drop too low, increase the output setting on the control unit.

## pH Level

pH should stay between 7.4 and 7.6. The electrolysis process tends to raise

pH over time, so you may need to add pH decreaser (sodium bisulfate) periodically. Keeping pH in the correct range ensures that chlorine remains effective and that the salt cell does not scale excessively.

## Alkalinity and Cyanuric Acid

Total alkalinity should be between 80 and 120 ppm to buffer pH changes. Cyanuric acid (stabilizer) should be between 30 and 50 ppm to protect chlorine from sunlight degradation. The manual advises against using stabilized chlorine tablets, as

they can cause cyanuric acid to build up too high. instructions for cleaning the cell:

## Salt Level

Check the salt level using test strips or a digital meter every two weeks. Salt does not evaporate, but it is lost through backwashing, splashing, and rainwater dilution. The control unit will display a "low salt" indicator if levels fall below 2000 ppm.

---

### CLEANING THE SALT CELL

---

The salt cell contains titanium plates that can accumulate calcium scale over time. Scale buildup reduces efficiency and can eventually damage the cell. The **Intex Krystal Clear Saltwater System Manual** provides clear

1. Turn off the pump and unplug the control unit.
2. Disconnect the hoses and remove the salt cell chamber from the plumbing.
3. Inspect the plates for white or gray scale deposits.
4. Mix a cleaning solution using one part muriatic acid to ten parts water. Always add acid to water, never water to acid.
5. Submerge the cell in the cleaning solution for 5 to 10 minutes, or until bubbling stops. Do not leave it longer than 15 minutes.

6. Rinse thoroughly with fresh water and reassemble.

Clean the cell at least once per month or whenever you notice reduced chlorine output. Some models have a cleaning indicator light that reminds you when it is time.

---

## **TROUBLESHOOTING COMMON ISSUES**

---

Even with proper care, you may encounter occasional problems. The Intex Krystal Clear Saltwater System Manual includes a troubleshooting section that covers the most common issues. Here are a few examples:

### **Low**

## **Chlorine Output**

Check the salt level first. If it is fine, inspect the cell for scale buildup. Also, verify that the water temperature is above 60°F, as the system is less efficient in cold water. If the output setting is at maximum and chlorine is still low, the cell may be nearing the end of its lifespan.

## **Error Codes on the Display**

Most models display error codes such as "E1" or "E2." E1 typically indicates a

low salt concentration. E2 often indicates a high salt concentration or a short circuit in the cell. Consult the **Intex Krystal Clear Saltwater System Manual** for the exact meaning of each code for your model.

## Water Not Flowing Through the Cell

Ensure the pump is running and the hoses are not kinked. Check that the filter cartridge is clean. A clogged filter reduces flow and can cause the system to shut down automatically.

## System Not Powering On

Verify that the GFCI outlet is working. Press the reset button on the outlet. If the unit still does not power on, inspect the power cord and connections for damage. Contact Intex customer support if necessary.

---

### SEASONAL MAINTENANCE AND WINTER STORAGE

---

At the end of the swimming season, you must winterize your saltwater system. The **Intex Krystal Clear Saltwater System Manual** provides these

steps:

- Remove the salt cell from the plumbing line.
- Clean the cell thoroughly with the acid solution described above.
- Store the cell and control unit in a dry, frost-free location. Freezing temperatures can crack the cell and damage internal electronics.
- Disconnect all hoses and store them separately.
- Cover the control unit to protect it from dust and moisture during storage.

When spring arrives, reinstall the system, refill the pool with fresh water, and add salt as needed. Run the

pump for 24 hours before activating the saltwater system.

---

## **SAFETY PRECAUTIONS YOU SHOULD NOT IGNORE**

---

The Intex Krystal Clear Saltwater System Manual contains important safety warnings. Here are the critical ones:

- **Always use a GFCI outlet.** This protects against electrical shock in wet environments.
- **Never operate the system without water flow.** Running the cell dry will destroy it within minutes.
- **Keep children away from the control unit and electrical**

**connections.**

- **Do not attempt to open the control unit casing.** There are no user-serviceable parts inside.
- **Handle muriatic acid with extreme caution.** Wear gloves, goggles, and protective clothing. Work in a well-ventilated area.

---

## TIPS FOR

## EXTENDING THE LIFE OF YOUR SALTWATER SYSTEM

---

With proper maintenance, your Intex Krystal Clear Saltwater System can last several seasons. Follow these best practices:

- Clean the cell regularly, but do not over-clean it. Excessive acid cleaning can wear down the titanium coating